



FLOW IP65 K55011

GENERAL DETAILS

USO	Outdoor, Indoor, Indoor, Outdoor
GARANTÍA	3 years, 3 years

ELECTRICAL DETAILS

FUENTE DE LUZ	LED, LED
POTENCIA	5 W, 5 W, 10W, 10W, 15 W, 15 W, 20 W, 20 W, 30 W, 30 W
TEMPERATURA DE COLOR	2700K, 2700K, 3000K, 3000K, 4000K, 4000K
FLUJO LUMÍNICO	510 Lm, 510 Lm, 550 Lm, 550 Lm, 590 Lm, 590 Lm, 631 Lm, 631 Lm, 1090 Lm, 1090 Lm, 1140 Lm, 1140 Lm, 1193 Lm, 1193 Lm, 1530 Lm, 1530 Lm, 1630 Lm, 1630 Lm, 1735 Lm, 1735 Lm, 2080 Lm, 2080 Lm, 2130 Lm, 2130 Lm, 2200 Lm, 2200 Lm, 3602 Lm, 3602 Lm, 3700 Lm, 3700 Lm, 3800 Lm, 3800 Lm
EFICIENCIA LUMÍNICA	79 Lm/W, 79 Lm/W, 85 Lm/W, 85 Lm/W, 88 Lm/W, 88 Lm/W, 91 Lm/W, 91 Lm/W, 94 Lm/W, 94 Lm/W, 95 Lm/W, 95 Lm/W, 102 Lm/W, 102 Lm/W, 107 Lm/W, 107 Lm/W, 110 Lm/W, 110 Lm/W
DIMABLE	No Dim, No Dim
DRIVER	Remote, Remote
CLASE DE SEGURIDAD	III, III
ÍNDICE DE REPRODUCCIÓN CROMÁTICA	90, 90
TENSIÓN	220-240 V, 220-240 V
FRECUENCIA	50-60 Hz, 50-60 Hz
VIDA UTIL	35.000 h, 35.000 h

GENERAL DIMENSIONS

DIMENSIÓN	8 mm, 8 mm, 10 mm, 10 mm
CORTE	100 mm, 100 mm, 26,3 mm, 26,3 mm, 33,3 mm, 33,3 mm, 50 mm, 50 mm
DIMENSIONES DE EMBALAJE	N/A

*Please might expect a max.15% figure reduction in finishes other than white