



# noon

K50800.02.RF.BK-BK.38.ST.8.40.DA




## GENERAL DETAILS

| | |
|---|---|
| INSTALLATION | recessed with frame |
| FINISHES ALUMINIUM | Black-Black |
| LIGHT DIRECTION | Fixed |
| BEAM ANGLE | 38° |
| INT/EXT IP DEGREE | IP 23 |
| MATERIAL | Aluminio/Policarbonato |
| IK DEGREE | IK03 |
| UTILIZATION | Indoor |
| WARRANTY | 3 years |

## ELECTRICAL DETAILS

| | |
|---|---|
| LAMP | LED |
| POWER | 7 W |
| COLOUR TEMPERATURE | 4000K |
| LUMINOUS FLUX | 595 lm |
| EFFICACY DIMMING | 79 Lm/W |
| DIMABLE | DALI |
| DRIVER | Remote |
| CLASS PROTECTION | II |
| COLOUR RENDERING INDEX | CRI >80 |
| VOLTAGE | 220-240 V |
| FRECUENCIA | 50-60 Hz |
| CURRENT INTENSITY | 160 mA |
| LIFE TIME | 35.000 h |

## GENERAL DIMENSIONS

| | |
|---|---|
| DIMENSIONS | Ø 83 mm |
| CUT OUT | Ø 75 mm |
| HEIGHT | h-835-mm |
| DIMENSIONES DE EMBALAJE | 95 × 95 × 110 mm |
| PESO NETO | 0.15 |

*Please might expect a max.15% figure reduction in finishes other than white