

nses tilt

K51301.02.RF.BK-BK.15.ST.9.40.DA

GENERAL DETAILS

INSTALLATION	recessed with frame
FINISHES ALUMINIUM	Black-Black
LIGHT DIRECTION	Orientable
TILTING DEGREES	15°
BEAM ANGLE	15°
INT/EXT IP DEGREE	IP 23
MATERIAL	Aluminum
IK DEGREE	IK 6
UTILIZATION	Indoor
WARRANTY	3 years

ELECTRICAL DETAILS

LAMP	LED
POWER	10W
COLOUR TEMPERATURE	4000K
LUMINOUS FLUX	660 Lm
EFFICACY DIMMING	57 Lm/W
DIMABLE	DALI
DRIVER	Remote
CLASS PROTECTION	II
COLOUR RENDERING INDEX	CRI>90
VOLTAGE	220-240 V
FRECUENCIA	50-60 Hz
CURRENT INTENSITY	700 mA
LIFE TIME	35.000 h

GENERAL DIMENSIONS

DIMENSIONS	167×58 mm
CUT OUT	155×45 mm
HEIGHT	h 48.5 mm
DIMENSIONES DE EMBALAJE	155 × 155 × 45 mm
PESO NETO	0.45

*Please might expect a max.15% figure reduction in finishes other than white