



nses tilt  
K51301.03.RF.BK-BK.15.ST.9.27.PC

## GENERAL DETAILS

|                    |                     |
|--------------------|---------------------|
| INSTALLATION       | recessed with frame |
| FINISHES ALUMINIUM | Black-Black         |
| LIGHT DIRECTION    | Orientable          |
| TILTING DEGREES    | 15°                 |
| BEAM ANGLE         | 15°                 |
| INT/EXT IP DEGREE  | IP 23               |
| MATERIAL           | Aluminum            |
| IK DEGREE          | IK 6                |
| UTILIZATION        | Indoor              |
| WARRANTY           | 3 years             |

## ELECTRICAL DETAILS

|                        |           |
|------------------------|-----------|
| LAMP                   | LED       |
| POWER                  | 20 W      |
| COLOUR TEMPERATURE     | 2700K     |
| LUMINOUS FLUX          | 1250 Lm   |
| EFFICACY DIMMING       | 63 Lm/W   |
| DIMABLE                | PHASE CUT |
| DRIVER                 | Remote    |
| CLASS PROTECTION       | II        |
| COLOUR RENDERING INDEX | CRI>90    |
| VOLTAGE                | 220-240 V |
| FRECUENCIA             | 50-60 Hz  |
| CURRENT INTENSITY      | 600 mA    |
| LIFE TIME              | 35.000 h  |

## GENERAL DIMENSIONS

|                         |                  |
|-------------------------|------------------|
| DIMENSIONS              | 300x58 mm        |
| CUT OUT                 | 290x45 mm        |
| HEIGHT                  | h 48.5 mm        |
| DIMENSIONES DE EMBALAJE | 325 x 80 x 85 mm |
| PESO NETO               | 0.78             |

\*Please might expect a max.15% figure reduction in finishes other than white