


# nses

K51300.02.TK.WH-BK.30.ST.9.40




## GENERAL DETAILS

| | |
|---|---|
| INSTALLATION | Tracklight |
| FINISHES ALUMINIUM | Black-White |
| LIGHT DIRECTION | Orientable |
| TILTING DEGREES | 60º |
| ROTATION DEGREES | 360° |
| BEAM ANGLE | 30° |
| INT/EXT IP DEGREE | IP20 |
| MATERIAL | Aluminum |
| IK DEGREE | IK 6 |
| UTILIZATION | Indoor |
| WARRANTY | 3 years |

## ELECTRICAL DETAILS

| | |
|---|---|
| LAMP | LED |
| POWER | 20 W |
| COLOUR TEMPERATURE | 4000K |
| LUMINOUS FLUX | 290 Lm |
| EFFICACY DIMMING | 58 Lm/W |
| DIMABLE | No Dim |
| DRIVER | Integrated |
| CLASS PROTECTION | II |
| COLOUR RENDERING INDEX | CRI>90 |
| VOLTAGE | 220-240 V |
| FRECUENCIA | 50-60 Hz |
| CURRENT INTENSITY | 600 mA |
| LIFE TIME | 35.000 h |

## GENERAL DIMENSIONS

| | |
|---|---|
| DIMENSIONS | 270×34.5 mm |
| HEIGHT | h 80 mm |
| DIMENSIONES DE EMBALAJE | 290 × 150 × 45 mm |
| PESO NETO | 0.80 |

*Please might expect a max.15% figure reduction in finishes other than white

Partida Madrigueres Sud 63A, Naves1-4, 03700 Dénia · Alicante (Spain) | Tel. 0034 96 575 3083 · info@kohl-lighting.com · www. kohl-lighting.com