


# versus

K51100.03.RF.BK-GL.38.ST.8.30




## GENERAL DETAILS

| | |
|---|---|
| INSTALLATION | recessed with frame |
| FINISHES ALUMINIUM | Black-Gold |
| LIGHT DIRECTION | Fixed |
| BEAM ANGLE | 38° |
| INT/EXT IP DEGREE | IP 23 |
| MATERIAL | Aluminum |
| IK DEGREE | IK03 |
| UTILIZATION | Indoor |
| WARRANTY | 3 years |

## ELECTRICAL DETAILS

| | |
|---|---|
| LAMP | LED |
| POWER | 15 W |
| COLOUR TEMPERATURE | 3000K |
| LUMINOUS FLUX | 1275 Lm |
| EFFICACY DIMMING | 91 Lm/W |
| DIMABLE | No Dim |
| DRIVER | Remote |
| CLASS PROTECTION | II |
| COLOUR RENDERING INDEX | CRI >80 |
| VOLTAGE | 220-240 V |
| FRECUENCIA | 50-60 Hz |
| CURRENT INTENSITY | 350 mA |
| LIFE TIME | 35.000 h |

## GENERAL DIMENSIONS

| | |
|---|---|
| DIMENSIONS | Ø 80 mm |
| CUT OUT | Ø 75 mm |
| HEIGHT | h 100 mm |
| DIMENSIONES DE EMBALAJE | 115 × 165 × 115 mm |
| PESO NETO | 0.38 |

*Please might expect a max.15% figure reduction in finishes other than white

Partida Madrigueres Sud 63A, Naves1-4, 03700 Dénia · Alicante (Spain) | Tel. 0034 96 575 3083 · info@kohl-lighting.com · www. kohl-lighting.com