




wally
K50700.01.WS.BK-BK.ST.8.30



GENERAL DETAILS

| | |
|--------------------|--------------|
| INSTALLATION | Wall Surface |
| FINISHES ALUMINIUM | Black-Black |
| LIGHT DIRECTION | Orientable |
| TILTING DEGREES | 45° |
| ROTATION DEGREES | 360° |
| INT/EXT IP DEGREE | IP20 |
| MATERIAL | Aluminum |
| IK DEGREE | IK010 |
| UTILIZATION | Indoor |
| WARRANTY | 3 years |

ELECTRICAL DETAILS

| | |
|------------------------|------------|
| LAMP | LED |
| POWER | 6 W |
| COLOUR TEMPERATURE | 3000K |
| LUMINOUS FLUX | 325 Lm |
| EFFICACY DIMMING | 50 Lm/W |
| DIMABLE | No Dim |
| DRIVER | Integrated |
| CLASS PROTECTION | I |
| COLOUR RENDERING INDEX | CRI >80 |
| VOLTAGE | 220-240 V |
| FRECUENCIA | 50-60 Hz |
| CURRENT INTENSITY | 300 mA |
| LIFE TIME | 35.000 h |

GENERAL DIMENSIONS

| | |
|-------------------------|--------------------|
| DIMENSIONS | 120X80 mm |
| HEIGHT | h 95 mm |
| DIMENSIONES DE EMBALAJE | 110 × 110 × 110 mm |

*Please might expect a max.15% figure reduction in finishes other than white