

chess elite k-select

K50523.RF

GENERAL DETAILS

INSTALLATION	recessed with frame
FINISHES ALUMINIUM	White-White
OPTIC COVER	Cielo, Microprismatico, Opal
LIGHT DIRECTION	Fixed
INT/EXT IP DEGREE	IP20/40
MATERIAL	Aluminum
IK DEGREE	IK03
UTILIZATION	Indoor
WARRANTY	5 years

ELECTRICAL DETAILS

LAMP	LED
POWER	40 W, 60 W
COLOUR TEMPERATURE	3CCT 3000K-4000K-6000K
LUMINOUS FLUX	3600-4000-3800 Lm, 3600-4000-3800 Lm*, 4250-4950-4450 Lm, 4400-5100-4600 Lm, 4400-5100-4600 Lm*
EFFICACY DIMMING	73-85-76 Lm/W, 76-87-79 Lm/W, 87-98-93 Lm/W, 91-101-96 Lm/W
DIMABLE	1.10v, DALI, No Dim, Push
DRIVER	Remote
CLASS PROTECTION	II
COLOUR RENDERING INDEX	CRI >80
VOLTAGE	220-240 V
CURRENT INTENSITY	1000 mA, 1500 mA
LIFE TIME	50.000 h

GENERAL DIMENSIONS

DIMENSIONS	595×595 mm, 1195×595 mm
CUT OUT	595×595 mm (techo modular), 1195×595 mm (techo modular)
HEIGHT	h 38 mm
DIMENSIONES DE EMBALAJE	N/A

*El difusor SK (SKY) es para fines decorativos (lúmenes no medibles)

*Please might expect a max.15% figure reduction in finishes other than white