



chess k-select
K50510.RF

GENERAL DETAILS

INSTALLATION	recessed with frame
FINISHES ALUMINIUM	White-White
OPTIC COVER	Cielo, Microprismatico, Opal
LIGHT DIRECTION	Fixed
INT/EXT IP DEGREE	IP20/40
MATERIAL	Aluminum
IK DEGREE	IK03
UTILIZATION	Indoor
WARRANTY	3 years

ELECTRICAL DETAILS

LAMP	LED
POWER	36 W, 40 W, 60 W
COLOUR TEMPERATURE	3CCT 3000K-4000K-6000K
LUMINOUS FLUX	2300-2700-2500 Lm, 2600-3000-2800 Lm, 2600-3000-2800 Lm*, 3450-3850-3650 Lm, 3600-4000-3800 Lm, 3600-4000-3800 Lm*, 4250-4950-4450 Lm, 4400-5100-4600 Lm, 4400-5100-4600 Lm*
EFFICACY DIMMING	67-79-73 Lm/W, 73-85-76 Lm/W, 74-87-81 Lm/W, 76-87-79 Lm/W, 87-98-93 Lm/W, 91-101-96 Lm/W
DIMABLE	1.10v, DALI, No Dim, Push
DRIVER	Remote
CLASS PROTECTION	II
COLOUR RENDERING INDEX	CRI >80
VOLTAGE	220-240 V
FRECUENCIA	50-60 Hz
CURRENT INTENSITY	900 mA, 1000 mA, 1500 mA
LIFE TIME	50.000h LB0B10

GENERAL DIMENSIONS

DIMENSIONS	595×595 mm, 1195×595 mm, 1195×295 mm
CUT OUT	1195×295 mm (techo modular), 1195×595 mm (techo modular), 595×595 mm (techo modular)
HEIGHT	h 8 mm
DIMENSIONES DE EMBALAJE	N/A

*Please might expect a max.15% figure reduction in finishes other than white