




chess k-select

K50510.02.RF.WH-WH.OP.ST.8.01.DA



GENERAL DETAILS

INSTALLATION	recessed with frame
FINISHES ALUMINIUM	White-White
OPTIC COVER	Opal
LIGHT DIRECTION	Fixed
INT/EXT IP DEGREE	IP 23
MATERIAL	Aluminum
IK DEGREE	IK03
UTILIZATION	Indoor
WARRANTY	3 years

ELECTRICAL DETAILS

LAMP	LED
POWER	36 W
COLOUR TEMPERATURE	3CCT 3000K-4000K-6000K
LUMINOUS FLUX	2600-3000-2800 Lm
EFFICACY DIMMING	74-87-81 Lm/W
DIMABLE	DALI
DRIVER	Remote
CLASS PROTECTION	II
COLOUR RENDERING INDEX	CRI >80
VOLTAGE	220-240 V
FRECUENCIA	50-60 Hz
CURRENT INTENSITY	900 mA
LIFE TIME	35.000 h

GENERAL DIMENSIONS

DIMENSIONS	1195×295 mm
CUT OUT	1195×295 mm (techo modular)
HEIGHT	h 8 mm
DIMENSIONES DE EMBALAJE	N/A
PESO NETO	2.32

*Please might expect a max.15% figure reduction in finishes other than white