

chess winner k-select

K50522.RF

GENERAL DETAILS

INSTALLATION	recessed with frame
FINISHES ALUMINIUM	White-White
OPTIC COVER	Cielo, Microprismatico, Opal
LIGHT DIRECTION	Fixed
INT/EXT IP DEGREE	IP20/40
MATERIAL	Aluminum
IK DEGREE	IK03
UTILIZATION	Indoor
WARRANTY	5 years

ELECTRICAL DETAILS

LAMP	LED
POWER	37 W, 60 W
COLOUR TEMPERATURE	3CCT 3000K-4000K-6000K
LUMINOUS FLUX	2700-3200-2900, 3000-3500-3200, 6000-6400-6250 Lm, 7400-7800-7650 Lm
EFFICACY DIMMING	74-88-80 Lm/W, 82-96-80 Lm/W, 107-114-110 Lm/W, 132-140-136 LM/W
DIMABLE	1.10v, DALI, No Dim, Push
DRIVER	Remote
CLASS PROTECTION	II
COLOUR RENDERING INDEX	CRI >80
VOLTAGE	220-240 V
CURRENT INTENSITY	1000 mA, 1500 mA
LIFE TIME	50.000 h

GENERAL DIMENSIONS

DIMENSIONS	595×595 mm, 1195×595 mm
CUT OUT	595×595 mm (techo modular), 1195×595 mm (techo modular)
HEIGHT	h 29 mm
DIMENSIONES DE EMBALAJE	N/A

*Please might expect a max.15% figure reduction in finishes other than white