



disc slim sq
K51705.RF

GENERAL DETAILS

INSTALLATION	recessed with frame
FINISHES ALUMINIUM	Black-Black, White-White
OPTIC COVER	Opal
LIGHT DIRECTION	Fixed
INT/EXT IP DEGREE	IP 23
MATERIAL	Aluminum
IK DEGREE	IK03
UTILIZATION	Indoor
WARRANTY	5 years

ELECTRICAL DETAILS

LAMP	LED
POWER	6 W, 12 W, 24 W
COLOUR TEMPERATURE	3000K, 4000K
LUMINOUS FLUX	445 Lm, 465 Lm, 1210 Lm, 1225 Lm, 2270 Lm, 2430 Lm
EFFICACY DIMMING	70 Lm/W, 74 Lm/W, 95 Lm/W, 97 Lm/W, 100 Lm/W
DIMABLE	1.10v, DALI, No Dim, PHASE CUT, Push
DRIVER	Remote
CLASS PROTECTION	II
COLOUR RENDERING INDEX	CRI >80
VOLTAGE	220-240 V
CURRENT INTENSITY	160 mA, 300 mA, 600 mA
LIFE TIME	50.000 h

GENERAL DIMENSIONS

DIMENSIONS	90×90 mm, 145×145 mm, 225×225 mm
CUT OUT	72×72 mm, 125×125 mm, 205×205 mm
HEIGHT	h 25 mm
DIMENSIONES DE EMBALAJE	N/A

*medidas .01 no regulación en phase cut

*Please might expect a max.15% figure reduction in finishes other than white