

disc sq

K51703.RF

GENERAL DETAILS

INSTALLATION	recessed with frame
FINISHES ALUMINIUM	Black-Black, White-White
LIGHT DIRECTION	Fixed
INT/EXT IP DEGREE	IP 43
MATERIAL	Aluminum
IK DEGREE	IK03
UTILIZATION	Indoor
WARRANTY	5 years

ELECTRICAL DETAILS

LAMP	LED
POWER	8 W, 12 W, 20 W, 24 W
COLOUR TEMPERATURE	3000K, 4000K
LUMINOUS FLUX	480 Lm, 490 Lm, 1040 Lm, 1060 Lm, 1750 Lm, 1800 lm, 2300 lm, 2350 Lm
EFFICACY DIMMING	62 Lm/W, 63 Lm/W, 83 Lm/W, 85 Lm/W, 90 Lm/W, 92 Lm/W, 98 Lm/W, 100 Lm/W
DIMABLE	1.10v, DALI, No Dim, PHASE CUT, Push
DRIVER	Remote
CLASS PROTECTION	II
COLOUR RENDERING INDEX	CRI >80
VOLTAGE	220-240 V
CURRENT INTENSITY	300 mA, 350 mA, 500 mA, 600 mA
LIFE TIME	50.000 h

GENERAL DIMENSIONS

DIMENSIONS	120×120 mm, 172×172 mm, 225×225 mm, 300×300 mm
CUT OUT	108×108 mm, 157x157 mm, 210x210 mm, 285x285 mm
HEIGHT	h 22 mm
DIMENSIONES DE EMBALAJE	N/A

*medidas .01 no regulación en phase cut

*Please might expect a max.15% figure reduction in finishes other than white