

disc tina deep sq

K50415.RF

GENERAL DETAILS

INSTALLATION	recessed with frame
FINISHES ALUMINIUM	White-White
LIGHT DIRECTION	Fixed
INT/EXT IP DEGREE	IP 23
MATERIAL	Aluminum
IK DEGREE	IK 6
UTILIZATION	Indoor
WARRANTY	5 years

ELECTRICAL DETAILS

LAMP	LED
POWER	8 W, 18 W
COLOUR TEMPERATURE	3000K, 4000K
LUMINOUS FLUX	500 Lm, 550 lm, 1300 Lm, 1390 Lm
EFFICACY DIMMING	60 Lm/W, 67 Lm/W, 78 Lm/W, 84 Lm/W
DIMABLE	1.10v, DALI, No Dim, PHASE CUT, Push
DRIVER	Remote
CLASS PROTECTION	II
COLOUR RENDERING INDEX	CRI >80
VOLTAGE	220-240 V
CURRENT INTENSITY	300 mA, 400 mA
LIFE TIME	50.000 h

GENERAL DIMENSIONS

DIMENSIONS	111×111 mm, 180×180 mm
CUT OUT	98x98 mm, 160x160 mm
HEIGHT	h 35 mm, h 55 mm
DIMENSIONES DE EMBALAJE	N/A

*Please might expect a max.15% figure reduction in finishes other than white