



eryl  
K51000.SR

## GENERAL DETAILS

|                    |                          |
|--------------------|--------------------------|
| INSTALLATION       | Surface                  |
| FINISHES ALUMINIUM | Black-Black, White-White |
| LIGHT DIRECTION    | Fixed                    |
| BEAM ANGLE         | 36°                      |
| INT/EXT IP DEGREE  | IP20                     |
| MATERIAL           | Aluminum                 |
| IK DEGREE          | IK 6                     |
| UTILIZATION        | Indoor                   |
| WARRANTY           | 3 years                  |

## ELECTRICAL DETAILS

|                        |   |
|------------------------|---|
| LAMP                   | LED   |
| POWER                  | 8 W, 12 W, 20 W                                     |
| COLOUR TEMPERATURE     | 3000K, 4000K  |
| LUMINOUS FLUX          | 570 lm, 592 lm, 888 lm, 920 lm, 1430 lm,<br>1520 lm |
| EFFICACY DIMMING       | 71 lm/W, 72 lm/W, 74 lm/W, 76 lm/W, 77 lm/W         |
| DIMABLE                | No Dim  |
| DRIVER                 | Integrated  |
| CLASS PROTECTION       | II  |
| COLOUR RENDERING INDEX | CRI >80   |
| VOLTAGE                | 220-240 V   |
| FRECUENCIA             | 50-60 Hz  |
| LIFE TIME              | 50.000 h  |

## GENERAL DIMENSIONS

|                         |                           |
|-------------------------|---------------------------|
| DIMENSIONS              | Ø 80 mm, Ø 65 mm, Ø 95 mm |
| HEIGHT                  | h 45 mm, h 55mm, h 65mm   |
| DIMENSIONES DE EMBALAJE | N/A                       |

\*Please might expect a max.15% figure reduction in finishes other than white