



eryl  
K51000.SR

## GENERAL DETAILS

INSTALLATION	Surface
FINISHES ALUMINIUM	Black-Black, White-White
LIGHT DIRECTION	Fixed
BEAM ANGLE	36°
INT/EXT IP DEGREE	IP20
MATERIAL	Aluminum
IK DEGREE	IK 6
UTILIZATION	Indoor
WARRANTY	3 years

## ELECTRICAL DETAILS

LAMP	LED
POWER	8 W, 12 W, 20 W
COLOUR TEMPERATURE	3000K, 4000K
LUMINOUS FLUX	570 lm, 592 lm, 888 lm, 920 lm, 1430 lm, 1520 lm
EFFICACY DIMMING	71 lm/W, 72 lm/W, 74 lm/W, 76 lm/W, 77 lm/W
DIMABLE	No Dim
DRIVER	Integrated
CLASS PROTECTION	II
COLOUR RENDERING INDEX	CRI >80
VOLTAGE	220-240 V
FRECUENCIA	50-60 Hz
LIFE TIME	35.000 h

## GENERAL DIMENSIONS

DIMENSIONS	Ø 80 mm, Ø 65 mm, Ø 95 mm
HEIGHT	h 45 mm, h 55mm, h 65mm
DIMENSIONES DE EMBALAJE	N/A

\*Please might expect a max.15% figure reduction in finishes other than white