

fame
K51500.TK

GENERAL DETAILS

INSTALLATION	Tracklight
FINISHES ALUMINIUM	Black-Black, White-White
LIGHT DIRECTION	Orientable
TILTING DEGREES	90°
ROTATION DEGREES	360°
BEAM ANGLE	38º, 60º
INT/EXT IP DEGREE	IP20
MATERIAL	Aluminum
IK DEGREE	IK02
UTILIZATION	Indoor
WARRANTY	5 years

ELECTRICAL DETAILS

LAMP	LED
POWER	10W, 20 W, 30 W
COLOUR TEMPERATURE	3000K, 4000K
LUMINOUS FLUX	830 lm, 850 lm, 1710 Lm, 1880 Lm, 2430 Lm, 2670 Lm
EFFICACY DIMMING	80 Lm/W, 82 Lm/W, 84 Lm/W, 85 Lm/W, 92 Lm/W, 93 Lm/W
DIMABLE	DALI, No Dim
DRIVER	Integrated
CLASS PROTECTION	II
COLOUR RENDERING INDEX	CRI >80
VOLTAGE	220-240 V
CURRENT INTENSITY	250 mA, 500 mA, 700 mA
LIFE TIME	50.000 h

GENERAL DIMENSIONS

DIMENSIONS	110 X Ø 55 mm, 155 x Ø 75 mm , 185 x Ø 75 mm
HEIGHT	h 95 mm, h 120 mm
DIMENSIONES DE EMBALAJE	N/A
PESO NETO	0.38

*Please might expect a max.15% figure reduction in finishes other than white