



**fame**  
K51500.TK

## GENERAL DETAILS

INSTALLATION	Tracklight
FINISHES ALUMINIUM	Black-Black, White-White
LIGHT DIRECTION	Orientable
TILTING DEGREES	90°
ROTATION DEGREES	360°
BEAM ANGLE	38°, 60°
INT/EXT IP DEGREE	IP20
MATERIAL	Aluminum
IK DEGREE	IK02
UTILIZATION	Indoor
WARRANTY	5 years

## ELECTRICAL DETAILS

LAMP	LED
POWER	10W, 20 W, 30 W
COLOUR TEMPERATURE	3000K, 4000K
LUMINOUS FLUX	830 lm, 850 lm, 1710 lm, 1880 lm, 2430 lm, 2670 lm
EFFICACY DIMMING	80 lm/W, 82 lm/W, 84 lm/W, 85 lm/W, 92 lm/W, 93 lm/W
DIMABLE	DALI, No Dim
DRIVER	Integrated
CLASS PROTECTION	II
COLOUR RENDERING INDEX	CRI >80
VOLTAGE	220-240 V
FRECUENCIA	50-60 Hz
CURRENT INTENSITY	250 mA, 500 mA, 700 mA
LIFE TIME	50.000 h

## GENERAL DIMENSIONS

DIMENSIONS	110 X Ø 55 mm, 155 x Ø 75 mm , 185 x Ø 75 mm
HEIGHT	h 120 mm, h 95 mm
DIMENSIONES DE EMBALAJE	N/A
PESO NETO	0.38

\*Please might expect a max.15% figure reduction in finishes other than white