


fame

K51500.02.TK.BK-BK.60.ST.8.30.DA



GENERAL DETAILS

INSTALLATION	Tracklight
FINISHES ALUMINIUM	Black-Black
LIGHT DIRECTION	Orientable
TILTING DEGREES	90°
ROTATION DEGREES	360°
BEAM ANGLE	60º
INT/EXT IP DEGREE	IP20
MATERIAL	Aluminum
IK DEGREE	IK02
UTILIZATION	Indoor
WARRANTY	5 years

ELECTRICAL DETAILS

LAMP	LED
POWER	20 W
COLOUR TEMPERATURE	3000K
LUMINOUS FLUX	1710 Lm
EFFICACY DIMMING	85 Lm/W
DIMABLE	DALI
DRIVER	Integrated
CLASS PROTECTION	II
COLOUR RENDERING INDEX	CRI >80
VOLTAGE	220-240 V
CURRENT INTENSITY	500 mA
LIFE TIME	50.000 h

GENERAL DIMENSIONS

DIMENSIONS	155 x Ø 75 mm
HEIGHT	h 95 mm, h 120 mm
DIMENSIONES DE EMBALAJE	205 × 225 × 95 mm
PESO NETO	0.38

*Please might expect a max.15% figure reduction in finishes other than white