




fame
K51500.02.TK.WH-WH.60.ST.8.30.DA



GENERAL DETAILS

| | |
|--------------------|-------------|
| INSTALLATION | Tracklight |
| FINISHES ALUMINIUM | White-White |
| LIGHT DIRECTION | Orientable |
| TILTING DEGREES | 90° |
| ROTATION DEGREES | 360° |
| BEAM ANGLE | 60° |
| INT/EXT IP DEGREE | IP20 |
| MATERIAL | Aluminum |
| IK DEGREE | IK02 |
| UTILIZATION | Indoor |
| WARRANTY | 5 years |

ELECTRICAL DETAILS

| | |
|------------------------|------------|
| LAMP | LED |
| POWER | 20 W |
| COLOUR TEMPERATURE | 3000K |
| LUMINOUS FLUX | 1710 Lm |
| EFFICACY DIMMING | 85 Lm/W |
| DIMABLE | DALI |
| DRIVER | Integrated |
| CLASS PROTECTION | II |
| COLOUR RENDERING INDEX | CRI >80 |
| VOLTAGE | 220-240 V |
| FRECUENCIA | 50-60 Hz |
| CURRENT INTENSITY | 500 mA |
| LIFE TIME | 50.000 h |

GENERAL DIMENSIONS

| | |
|-------------------------|-------------------|
| DIMENSIONS | 155 x Ø 75 mm |
| HEIGHT | h 120 mm, h 95 mm |
| DIMENSIONES DE EMBALAJE | 205 x 225 x 95 mm |
| PESO NETO | 0.38 |

*Please might expect a max.15% figure reduction in finishes other than white