

lim miranda sq

K53105.RF

GENERAL DETAILS

INSTALLATION	recessed with frame
FINISHES ALUMINIUM	White-White
OPTIC COVER	Opal
LIGHT DIRECTION	Fixed
INT/EXT IP DEGREE	IP 44
MATERIAL	Aluminum
IK DEGREE	IK03
UTILIZATION	Indoor
WARRANTY	5 years

ELECTRICAL DETAILS

LAMP	LED
POWER	8 W, 15 W, 22 W
COLOUR TEMPERATURE	3000K, 4000K
LUMINOUS FLUX	650 Lm, 730 Lm, 1250 Lm, 1400 Lm, 1700 Lm, 1900 lm
EFFICACY DIMMING	70 Lm/W, 73 Lm/W, 79 Lm/W, 80 Lm/W, 81 Lm/W, 90 Lm/W
DIMABLE	1.10v, DALI, No Dim, PHASE CUT, Push
DRIVER	Remote
CLASS PROTECTION	II
COLOUR RENDERING INDEX	CRI >80
VOLTAGE	220-240 V
CURRENT INTENSITY	200 mA, 350 mA, 600 mA
LIFE TIME	50.000 h

GENERAL DIMENSIONS

DIMENSIONS	120×120 mm, 172×172 mm, 225×225 mm
CUT OUT	115x115 mm, 160x160 mm, 215×215 mm
HEIGHT	h 27 mm
DIMENSIONES DE EMBALAJE	N/A

*Please might expect a max.15% figure reduction in finishes other than white