



lim sq

K50321.04.RF.BK-BK.MP.ST.8.40.PU



GENERAL DETAILS

INSTALLATION	recessed with frame
FINISHES ALUMINIUM	Black-Black
OPTIC COVER	Microprismatico
LIGHT DIRECTION	Fixed
INT/EXT IP DEGREE	IP 44
MATERIAL	Aluminum
IK DEGREE	IK 6
UTILIZATION	Indoor
WARRANTY	5 years

ELECTRICAL DETAILS

LAMP	LED
POWER	30 W
COLOUR TEMPERATURE	4000K
LUMINOUS FLUX	3110 Lm
EFFICACY DIMMING	104 Lm/W
DIMABLE	Push
DRIVER	Remote
CLASS PROTECTION	II
COLOUR RENDERING INDEX	CRI >80
VOLTAGE	220-240 V
CURRENT INTENSITY	750 mA
LIFE TIME	50.000 h

GENERAL DIMENSIONS

DIMENSIONS	210×210 mm
CUT OUT	Ø 200 mm
HEIGHT	h 60 mm
DIMENSIONES DE EMBALAJE	220 × 220 × 70 mm
PESO NETO	0.65

*Please might expect a max.15% figure reduction in finishes other than white

Partida Madrigueres Sud 63A, Naves1-4, 03700 Dénia · Alicante (Spain) | Tel. 0034 96 575 3083 · info@kohl-lighting.com · www. kohl-lighting.com