




lim sq
K50321.04.RF.WH-WH.MP.ST.8.30.PU



GENERAL DETAILS

| | |
|--------------------|---------------------|
| INSTALLATION | recessed with frame |
| FINISHES ALUMINIUM | White-White |
| OPTIC COVER | Microprismatico |
| LIGHT DIRECTION | Fixed |
| INT/EXT IP DEGREE | IP 44 |
| MATERIAL | Aluminum |
| IK DEGREE | IK 6 |
| UTILIZATION | Indoor |
| WARRANTY | 3 years |

ELECTRICAL DETAILS

| | |
|------------------------|-----------|
| LAMP | LED |
| POWER | 30 W |
| COLOUR TEMPERATURE | 3000K |
| LUMINOUS FLUX | 3080 lm |
| EFFICACY DIMMING | 103 Lm/W |
| DIMABLE | Push |
| DRIVER | Remote |
| CLASS PROTECTION | II |
| COLOUR RENDERING INDEX | CRI >80 |
| VOLTAGE | 220-240 V |
| FRECUENCIA | 50-60 Hz |
| CURRENT INTENSITY | 750 mA |
| LIFE TIME | 35.000 h |

GENERAL DIMENSIONS

| | |
|-------------------------|-------------------|
| DIMENSIONS | 210×210 mm |
| CUT OUT | Ø 200 mm |
| HEIGHT | h 60 mm |
| DIMENSIONES DE EMBALAJE | 220 × 220 × 70 mm |
| PESO NETO | 0.65 |

*Please might expect a max.15% figure reduction in finishes other than white