




lim

K50320.01.RF.WH-WH.MP.ST.8.30.D1



GENERAL DETAILS

INSTALLATION	recessed with frame
FINISHES ALUMINIUM	White-White
OPTIC COVER	Microprismatico
LIGHT DIRECTION	Fixed
INT/EXT IP DEGREE	IP 44
MATERIAL	Aluminum
IK DEGREE	IK 6
UTILIZATION	Indoor
WARRANTY	3 years

ELECTRICAL DETAILS

LAMP	LED
POWER	7 W
COLOUR TEMPERATURE	3000K
LUMINOUS FLUX	530 lm
EFFICACY DIMMING	76 Lm/W
DIMABLE	1.10v
DRIVER	Remote
CLASS PROTECTION	II
COLOUR RENDERING INDEX	CRI >80
VOLTAGE	220-240 V
FRECUENCIA	50-60 Hz
CURRENT INTENSITY	300 mA
LIFE TIME	50.000 h

GENERAL DIMENSIONS

DIMENSIONS	Ø 103 mm
CUT OUT	Ø 90 mm
HEIGHT	h 56,5 mm
DIMENSIONES DE EMBALAJE	145 × 145 × 70 mm
PESO NETO	0.24

*Please might expect a max.15% figure reduction in finishes other than white