




**lim**  
K50320.03.RF.BK-BK.MP.ST.8.30.D1



## GENERAL DETAILS

INSTALLATION	recessed with frame
FINISHES ALUMINIUM	Black-Black
OPTIC COVER	Microprismatico
LIGHT DIRECTION	Fixed
INT/EXT IP DEGREE	IP 44
MATERIAL	Aluminum
IK DEGREE	IK 6
UTILIZATION	Indoor
WARRANTY	3 years

## ELECTRICAL DETAILS

LAMP	LED
POWER	25 W
COLOUR TEMPERATURE	3000K
LUMINOUS FLUX	2200 Lm
EFFICACY DIMMING	92 Lm/W
DIMABLE	1.10v
DRIVER	Remote
CLASS PROTECTION	II
COLOUR RENDERING INDEX	CRI >80
VOLTAGE	220-240 V
FRECUENCIA	50-60 Hz
CURRENT INTENSITY	600 mA
LIFE TIME	50.000 h

## GENERAL DIMENSIONS

DIMENSIONS	Ø 176 mm
CUT OUT	Ø 160 mm
HEIGHT	h 60 mm
DIMENSIONES DE EMBALAJE	220 × 220 × 70 mm
PESO NETO	0.55

\*Please might expect a max.15% figure reduction in finishes other than white