




**lumo mini**  
K51302.10.RF.BK-BK.38.ST.9.27



## GENERAL DETAILS

|                    |                     |
|--------------------|---------------------|
| INSTALLATION       | recessed with frame |
| FINISHES ALUMINIUM | Black-Black         |
| LIGHT DIRECTION    | Fixed               |
| BEAM ANGLE         | 38°                 |
| INT/EXT IP DEGREE  | IP20/23             |
| MATERIAL           | Aluminum            |
| IK DEGREE          | IK 6                |
| UTILIZATION        | Indoor              |
| WARRANTY           | 5 years             |

## ELECTRICAL DETAILS

|                        |           |
|------------------------|-----------|
| LAMP                   | LED       |
| POWER                  | 16 W      |
| COLOUR TEMPERATURE     | 2700K     |
| LUMINOUS FLUX          | 1204 Lm   |
| EFFICACY DIMMING       | 75 Lm/W   |
| DIMABLE                | No Dim    |
| DRIVER                 | Remote    |
| CLASS PROTECTION       | II        |
| COLOUR RENDERING INDEX | CRI>90    |
| VOLTAGE                | 220-240 V |
| CURRENT INTENSITY      | 500 mA    |
| LIFE TIME              | 50.000 h  |

## GENERAL DIMENSIONS

|                         |                |
|-------------------------|----------------|
| DIMENSIONS              | .10 (190x28mm) |
| CUT OUT                 | 186x24 mm      |
| HEIGHT                  | h 38 mm        |
| DIMENSIONES DE EMBALAJE | N/A            |

\*Please might expect a max.15% figure reduction in finishes other than white