

GENERAL DETAILS

INSTALLATION	Trimless
FINISHES ALUMINIUM	Black-Black
LIGHT DIRECTION	Fixed
BEAM ANGLE	38º, 28º, 50º
INT/EXT IP DEGREE	IP20/23
MATERIAL	Aluminum
IK DEGREE	IK 6
UTILIZATION	Indoor
WARRANTY	5 years

ELECTRICAL DETAILS

LAMP	LED
POWER	5 W, 6,5W, 8 W, 14,5W, 16 W
COLOUR TEMPERATURE	2700K, 3000K, 4000K
LUMINOUS FLUX	361 Lm, 385 Lm, 439 Lm, 482 Lm, 510 Lm, 585 Lm, 602 Lm, 638 Lm, 731 Lm, 1084 Lm, 1204 Lm, 1261 Lm, 1316 Lm, 1463 Lm
EFFICACY DIMMING	72 Lm/W, 74 Lm/W, 75 Lm/W, 77 Lm/W, 78 Lm/W, 79 Lm/W, 80 Lm/W, 87 Lm/W, 88 Lm/W, 90 Lm/W, 91 Lm/W
DIMABLE	DALI, No Dim, Push
DRIVER	Remote
CLASS PROTECTION	II
COLOUR RENDERING INDEX	CRI>90
VOLTAGE	220-240 V
CURRENT INTENSITY	500 mA
LIFE TIME	50.000 h

GENERAL DIMENSIONS

DIMENSIONS	.03 (84x84mm), .05 (120x48mm), .10 (210x48mm), .22 (66x66mm), .33 (84x48mm)
CUT OUT	54x48 mm, 72x30 mm, 72x66 mm, 108x30 mm, 197x30 mm
HEIGHT	h 40 mm
DIMENSIONES DE EMBALAJE	N/A

*Please might expect a max.15% figure reduction in finishes other than white

lumo mini
K51302.TR