



luxo dara
K50300.02.RF.WH-WH.60.ST.9.40.D1

GENERAL DETAILS

INSTALLATION	recessed with frame
FINISHES ALUMINIUM	White-White
LIGHT DIRECTION	Fixed
BEAM ANGLE	60°
INT/EXT IP DEGREE	IP 54
MATERIAL	Aluminum
IK DEGREE	IK 6
UTILIZATION	Indoor
WARRANTY	3 years

ELECTRICAL DETAILS

LAMP	LED
POWER	20 W
COLOUR TEMPERATURE	4000K
LUMINOUS FLUX	1830 Lm
EFFICACY DIMMING	88 Lm/W
DIMABLE	1.10v
DRIVER	Remote
CLASS PROTECTION	II
COLOUR RENDERING INDEX	CRI>90
VOLTAGE	220-240 V
FRECUENCIA	50-60 Hz
CURRENT INTENSITY	500 mA
LIFE TIME	35.000 h

GENERAL DIMENSIONS

DIMENSIONS	Ø 160 mm
CUT OUT	Ø 145 mm
HEIGHT	h 110 mm
DIMENSIONES DE EMBALAJE	N/A
PESO NETO	0.80

*Please might expect a max.15% figure reduction in finishes other than white