



luxo dara
K50300.03.RF.WH-WH.40.ST.9.30.D1

GENERAL DETAILS

INSTALLATION	recessed with frame
FINISHES ALUMINIUM	White-White
LIGHT DIRECTION	Fixed
BEAM ANGLE	40°
INT/EXT IP DEGREE	IP 54
MATERIAL	Aluminum
IK DEGREE	IK 6
UTILIZATION	Indoor
WARRANTY	3 years

ELECTRICAL DETAILS

LAMP	LED
POWER	30 W
COLOUR TEMPERATURE	3000K
LUMINOUS FLUX	3060 Lm
EFFICACY DIMMING	102 Lm/W
DIMABLE	1.10v
DRIVER	Remote
CLASS PROTECTION	II
COLOUR RENDERING INDEX	CRI>90
VOLTAGE	220-240 V
FRECUENCIA	50-60 Hz
CURRENT INTENSITY	750 mA
LIFE TIME	50.000 h

GENERAL DIMENSIONS

DIMENSIONS	Ø 190 mm
CUT OUT	Ø 175 mm
HEIGHT	h 130 mm
DIMENSIONES DE EMBALAJE	N/A
PESO NETO	0.94

*Please might expect a max.15% figure reduction in finishes other than white