



luxo dara
K50300.03.RF.WH-WH.40.ST.9.30.PU

GENERAL DETAILS

| | |
|--------------------|---------------------|
| INSTALLATION | recessed with frame |
| FINISHES ALUMINIUM | White-White |
| LIGHT DIRECTION | Fixed |
| BEAM ANGLE | 40° |
| INT/EXT IP DEGREE | IP 54 |
| MATERIAL | Aluminum |
| IK DEGREE | IK 6 |
| UTILIZATION | Indoor |
| WARRANTY | 3 years |

ELECTRICAL DETAILS

| | |
|------------------------|-----------|
| LAMP | LED |
| POWER | 30 W |
| COLOUR TEMPERATURE | 3000K |
| LUMINOUS FLUX | 3060 Lm |
| EFFICACY DIMMING | 102 Lm/W |
| DIMABLE | Push |
| DRIVER | Remote |
| CLASS PROTECTION | II |
| COLOUR RENDERING INDEX | CRI>90 |
| VOLTAGE | 220-240 V |
| FRECUENCIA | 50-60 Hz |
| CURRENT INTENSITY | 750 mA |
| LIFE TIME | 35.000 h |

GENERAL DIMENSIONS

| | |
|-------------------------|----------|
| DIMENSIONS | Ø 190 mm |
| CUT OUT | Ø 175 mm |
| HEIGHT | h 130 mm |
| DIMENSIONES DE EMBALAJE | N/A |
| PESO NETO | 0.94 |

*Please might expect a max.15% figure reduction in finishes other than white