



luxo tilt
K50151.01.RF.BK-BK.25.ST.9.27



GENERAL DETAILS

| | |
|--------------------|---------------------|
| INSTALLATION | recessed with frame |
| FINISHES ALUMINIUM | Black-Black |
| LIGHT DIRECTION | Orientable |
| TILTING DEGREES | 20° |
| BEAM ANGLE | 25° |
| INT/EXT IP DEGREE | IP 32 |
| MATERIAL | Aluminum |
| IK DEGREE | IK05 |
| UTILIZATION | Indoor |
| WARRANTY | 3 years |

ELECTRICAL DETAILS

| | |
|------------------------|-----------|
| LAMP | LED |
| POWER | 12 W |
| COLOUR TEMPERATURE | 2700K |
| LUMINOUS FLUX | 810 Lm |
| EFFICACY DIMMING | 63 Lm/W |
| DIMABLE | No Dim |
| DRIVER | Remote |
| CLASS PROTECTION | II |
| COLOUR RENDERING INDEX | CRI>90 |
| VOLTAGE | 220-240 V |
| FRECUENCIA | 50-60 Hz |
| CURRENT INTENSITY | 300 mA |
| LIFE TIME | 50.000 h |

GENERAL DIMENSIONS

| | |
|-------------------------|--------------------|
| DIMENSIONS | Ø 105 mm |
| CUT OUT | Ø 95 mm |
| HEIGHT | h 73 mm |
| DIMENSIONES DE EMBALAJE | 100 × 100 × 100 mm |
| PESO NETO | 0.28 |

*Please might expect a max.15% figure reduction in finishes other than white