




**luxo tilt**  
K50151.01.RF.WH-WH.15.ST.9.40



## GENERAL DETAILS

|                    |                     |
|--------------------|---------------------|
| INSTALLATION       | recessed with frame |
| FINISHES ALUMINIUM | White-White         |
| LIGHT DIRECTION    | Orientable          |
| TILTING DEGREES    | 20°                 |
| BEAM ANGLE         | 15°                 |
| INT/EXT IP DEGREE  | IP 32               |
| MATERIAL           | Aluminum            |
| IK DEGREE          | IK05                |
| UTILIZATION        | Indoor              |
| WARRANTY           | 5 years             |

## ELECTRICAL DETAILS

|                        |           |
|------------------------|-----------|
| LAMP                   | LED       |
| POWER                  | 12 W      |
| COLOUR TEMPERATURE     | 4000K     |
| LUMINOUS FLUX          | 880 Lm    |
| EFFICACY DIMMING       | 68 Lm/W   |
| DIMABLE                | No Dim    |
| DRIVER                 | Remote    |
| CLASS PROTECTION       | II        |
| COLOUR RENDERING INDEX | CRI>90    |
| VOLTAGE                | 220-240 V |
| CURRENT INTENSITY      | 300 mA    |
| LIFE TIME              | 50.000 h  |

## GENERAL DIMENSIONS

|                         |                    |
|-------------------------|--------------------|
| DIMENSIONS              | Ø 105 mm           |
| CUT OUT                 | Ø 95 mm            |
| HEIGHT                  | h 73 mm            |
| DIMENSIONES DE EMBALAJE | 100 × 100 × 100 mm |
| PESO NETO               | 0.28               |

\*Please might expect a max.15% figure reduction in finishes other than white