


# luxo tilt

K50151.01.RF.WH-WH.38.ST.9.40




## GENERAL DETAILS

| | |
|---|---|
| INSTALLATION | recessed with frame |
| FINISHES ALUMINIUM | White-White |
| LIGHT DIRECTION | Orientable |
| TILTING DEGREES | 20º |
| BEAM ANGLE | 38º |
| INT/EXT IP DEGREE | IP 32 |
| MATERIAL | Aluminum |
| IK DEGREE | IK05 |
| UTILIZATION | Indoor |
| WARRANTY | 5 years |

## ELECTRICAL DETAILS

| | |
|---|---|
| LAMP | LED |
| POWER | 12 W |
| COLOUR TEMPERATURE | 4000K |
| LUMINOUS FLUX | 880 Lm |
| EFFICACY DIMMING | 68 Lm/W |
| DIMABLE | No Dim |
| DRIVER | Remote |
| CLASS PROTECTION | II |
| COLOUR RENDERING INDEX | CRI>90 |
| VOLTAGE | 220-240 V |
| CURRENT INTENSITY | 300 mA |
| LIFE TIME | 50.000 h |

## GENERAL DIMENSIONS

| | |
|---|---|
| DIMENSIONS | Ø 105 mm |
| CUT OUT | Ø 95 mm |
| HEIGHT | h 73 mm |
| DIMENSIONES DE EMBALAJE | 100 × 100 × 100 mm |
| PESO NETO | 0.28 |

*Please might expect a max.15% figure reduction in finishes other than white

Partida Madrigueres Sud 63A, Naves1-4, 03700 Dénia · Alicante (Spain) | Tel. 0034 96 575 3083 · info@kohl-lighting.com · www. kohl-lighting.com