



GENERAL DETAILS

| | |
|--------------------|---------------------|
| INSTALLATION | recessed with frame |
| FINISHES ALUMINIUM | White-White |
| LIGHT DIRECTION | Fixed |
| BEAM ANGLE | 15° |
| INT/EXT IP DEGREE | IP 32 |
| MATERIAL | Aluminum |
| IK DEGREE | IK05 |
| UTILIZATION | Indoor |
| WARRANTY | 3 years |

ELECTRICAL DETAILS

| | |
|------------------------|-----------|
| LAMP | LED |
| POWER | 12 W |
| COLOUR TEMPERATURE | 4000K |
| LUMINOUS FLUX | 1130 Lm |
| EFFICACY DIMMING | 90 Lm/W |
| DIMABLE | 1.10v |
| DRIVER | Remote |
| CLASS PROTECTION | II |
| COLOUR RENDERING INDEX | CRI>90 |
| VOLTAGE | 220-240 V |
| FRECUENCIA | 50-60 Hz |
| CURRENT INTENSITY | 250 mA |
| LIFE TIME | 35.000 h |

GENERAL DIMENSIONS

| | |
|-------------------------|--------------------|
| DIMENSIONS | Ø 100 mm |
| CUT OUT | Ø 90 mm |
| HEIGHT | h 75 mm |
| DIMENSIONES DE EMBALAJE | 100 × 100 × 100 mm |
| PESO NETO | 0.28 |

*Please might expect a max.15% figure reduction in finishes other than white

luxo
K50150.02.RF.WH-WH.15.ST.9.40.D1

