




luxo
K50150.03.RF.BK-BK.38.ST.9.30.D1



GENERAL DETAILS

| | |
|--------------------|---------------------|
| INSTALLATION | recessed with frame |
| FINISHES ALUMINIUM | Black-Black |
| LIGHT DIRECTION | Fixed |
| BEAM ANGLE | 38° |
| INT/EXT IP DEGREE | IP 32 |
| MATERIAL | Aluminum |
| IK DEGREE | IK05 |
| UTILIZATION | Indoor |
| WARRANTY | 3 years |

ELECTRICAL DETAILS

| | |
|------------------------|-----------|
| LAMP | LED |
| POWER | 20 W |
| COLOUR TEMPERATURE | 3000K |
| LUMINOUS FLUX | 1890 Lm |
| EFFICACY DIMMING | 90 Lm/W |
| DIMABLE | 1.10v |
| DRIVER | Remote |
| CLASS PROTECTION | II |
| COLOUR RENDERING INDEX | CRI>90 |
| VOLTAGE | 220-240 V |
| FRECUENCIA | 50-60 Hz |
| CURRENT INTENSITY | 500 mA |
| LIFE TIME | 35.000 h |

GENERAL DIMENSIONS

| | |
|-------------------------|--------------------|
| DIMENSIONS | Ø 120 mm |
| CUT OUT | Ø 113 mm |
| HEIGHT | h 98 mm |
| DIMENSIONES DE EMBALAJE | 125 × 125 × 115 mm |
| PESO NETO | 0.50 |

*Please might expect a max.15% figure reduction in finishes other than white