




**noon asymmetric**  
K50804.01.RF.BK-BK.38.ST.8.40.D1



## GENERAL DETAILS

|                    |                        |
|--------------------|------------------------|
| INSTALLATION       | recessed with frame    |
| FINISHES ALUMINIUM | Black-Black            |
| LIGHT DIRECTION    | Fixed                  |
| BEAM ANGLE         | 38°                    |
| INT/EXT IP DEGREE  | IP 23                  |
| MATERIAL           | Aluminio/Polycarbonato |
| IK DEGREE          | IK03                   |
| UTILIZATION        | Indoor                 |
| WARRANTY           | 3 years                |

## ELECTRICAL DETAILS

|                        |           |
|------------------------|-----------|
| LAMP                   | LED       |
| POWER                  | 7 W       |
| COLOUR TEMPERATURE     | 4000K     |
| LUMINOUS FLUX          | 595 lm    |
| EFFICACY DIMMING       | 79 Lm/W   |
| DIMABLE                | 1.10v     |
| DRIVER                 | Remote    |
| CLASS PROTECTION       | II        |
| COLOUR RENDERING INDEX | CRI >80   |
| VOLTAGE                | 220-240 V |
| FRECUENCIA             | 50-60 Hz  |
| CURRENT INTENSITY      | 160 mA    |
| LIFE TIME              | 35.000 h  |

## GENERAL DIMENSIONS

|                         |                    |
|-------------------------|--------------------|
| DIMENSIONS              | Ø 93 mm            |
| CUT OUT                 | Ø 85 mm            |
| HEIGHT                  | h 100 mm           |
| DIMENSIONES DE EMBALAJE | 105 × 105 × 120 mm |
| PESO NETO               | 0.15               |

\*Please might expect a max.15% figure reduction in finishes other than white