



noon
K50800.01.RF.WH-GL.38.ST.8.27.PU



GENERAL DETAILS

INSTALLATION	recessed with frame
FINISHES ALUMINIUM	White-Gold
LIGHT DIRECTION	Fixed
BEAM ANGLE	38°
INT/EXT IP DEGREE	IP 23
MATERIAL	Aluminio/Polycarbonato
IK DEGREE	IK03
UTILIZATION	Indoor
WARRANTY	3 years

ELECTRICAL DETAILS

LAMP	LED
POWER	5 W
COLOUR TEMPERATURE	2700K
LUMINOUS FLUX	470 Lm
EFFICACY DIMMING	78 Lm/W
DIMABLE	Push
DRIVER	Remote
CLASS PROTECTION	II
COLOUR RENDERING INDEX	CRI >80
VOLTAGE	220-240 V
FRECUENCIA	50-60 Hz
CURRENT INTENSITY	135 mA
LIFE TIME	50.000 h

GENERAL DIMENSIONS

DIMENSIONS	Ø 70 mm
CUT OUT	Ø 62 mm
HEIGHT	h 80 mm
DIMENSIONES DE EMBALAJE	N/A
PESO NETO	0.15

*Please might expect a max.15% figure reduction in finishes other than white