



**nses**  
K51300.05.RF.BK-BK.30.ST.9.30.D1



## GENERAL DETAILS

|                    |                     |
|--------------------|---------------------|
| INSTALLATION       | recessed with frame |
| FINISHES ALUMINIUM | Black-Black         |
| LIGHT DIRECTION    | Fixed               |
| BEAM ANGLE         | 30°                 |
| INT/EXT IP DEGREE  | IP20/23             |
| MATERIAL           | Aluminum            |
| IK DEGREE          | IK 6                |
| UTILIZATION        | Indoor              |
| WARRANTY           | 3 years             |

## ELECTRICAL DETAILS

|                        |           |
|------------------------|-----------|
| LAMP                   | LED       |
| POWER                  | 20 W      |
| COLOUR TEMPERATURE     | 3000K     |
| LUMINOUS FLUX          | 1530 Lm   |
| EFFICACY DIMMING       | 73 Lm/W   |
| DIMABLE                | 1.10v     |
| DRIVER                 | Remote    |
| CLASS PROTECTION       | II        |
| COLOUR RENDERING INDEX | CRI>90    |
| VOLTAGE                | 220-240 V |
| FRECUENCIA             | 50-60 Hz  |
| CURRENT INTENSITY      | 600 mA    |
| LIFE TIME              | 35.000 h  |

## GENERAL DIMENSIONS

|                         |                  |
|-------------------------|------------------|
| DIMENSIONS              | 280×45 mm        |
| CUT OUT                 | 273×37 mm        |
| DIMENSIONES DE EMBALAJE | 325 × 80 × 85 mm |
| PESO NETO               | 60               |

\*Please might expect a max.15% figure reduction in finishes other than white