



nses
K51300.02.RF.WH-BK.15.ST.9.27



GENERAL DETAILS

| | |
|--------------------|---------------------|
| INSTALLATION | recessed with frame |
| FINISHES ALUMINIUM | Black-White |
| LIGHT DIRECTION | Fixed |
| BEAM ANGLE | 15° |
| INT/EXT IP DEGREE | IP20/23 |
| MATERIAL | Aluminum |
| IK DEGREE | IK 6 |
| UTILIZATION | Indoor |
| WARRANTY | 3 years |

ELECTRICAL DETAILS

| | |
|------------------------|---|
| LAMP | LED |
| POWER | 4 W |
| COLOUR TEMPERATURE | 2700K |
| LUMINOUS FLUX | 335 Lm |
| EFFICACY DIMMING | 58 Lm/W, 62 Lm/W, 65 Lm/W, 67 Lm/W, 68 Lm/W, 69 Lm/W, 70 Lm/W, 71 Lm/W, 73 Lm/W, 74 Lm/W, 76 Lm/W, 78 Lm/W, 80 Lm/W |
| DIMABLE | No Dim |
| DRIVER | Remote |
| CLASS PROTECTION | II |
| COLOUR RENDERING INDEX | CRI>90 |
| VOLTAGE | 220-240 V |
| FRECUENCIA | 50-60 Hz |
| CURRENT INTENSITY | 700 mA |
| LIFE TIME | 50.000 h |

GENERAL DIMENSIONS

| | |
|-------------------------|------------------|
| DIMENSIONS | 75×45 mm |
| CUT OUT | 68×37 mm |
| DIMENSIONES DE EMBALAJE | 115 × 85 × 80 mm |
| PESO NETO | 18 |

*Please might expect a max.15% figure reduction in finishes other than white