



n ses tilt
K51301.RF

GENERAL DETAILS

INSTALLATION	recessed with frame
FINISHES ALUMINIUM	Black-Black, Black-White
LIGHT DIRECTION	Orientable
TILTING DEGREES	15°
ROTATION DEGREES	0°
BEAM ANGLE	15°, 30°, 45°
INT/EXT IP DEGREE	IP 23
MATERIAL	Aluminum
IK DEGREE	IK 6
UTILIZATION	Indoor
WARRANTY	3 years

ELECTRICAL DETAILS

LAMP	LED
POWER	6 W, 10W, 20 W
COLOUR TEMPERATURE	2700K, 3000K, 4000K
LUMINOUS FLUX	480 Lm, 520 Lm, 560 Lm, 835 Lm, 875 Lm, 915 Lm, 1430 Lm, 1530 Lm, 1630 Lm
EFFICACY DIMMING	68 Lm/W, 69 Lm/W, 70 Lm/W, 73 Lm/W, 74 Lm/W, 76 Lm/W, 78 Lm/W, 80 Lm/W
DIMABLE	1.10v, DALI, No Dim, PHASE CUT, Push
DRIVER	Remote
CLASS PROTECTION	II
COLOUR RENDERING INDEX	CRI>90
VOLTAGE	220-240 V
FRECUENCIA	50-60 Hz
CURRENT INTENSITY	600 mA, 700 mA
LIFE TIME	35.000 h

GENERAL DIMENSIONS

DIMENSIONS	123×58 mm, 167×58 mm, 300×58 mm
CUT OUT	115×45 mm, 155×45 mm, 290×45 mm
HEIGHT	h 48.5 mm
DIMENSIONES DE EMBALAJE	N/A

*Please might expect a max.15% figure reduction in finishes other than white