



**nses tilt**  
K51301.01.RF.BK-BK.15.ST.9.30.PU

## GENERAL DETAILS

|                    |                     |
|--------------------|---------------------|
| INSTALLATION       | recessed with frame |
| FINISHES ALUMINIUM | Black-Black         |
| LIGHT DIRECTION    | Orientable          |
| TILTING DEGREES    | 15°                 |
| ROTATION DEGREES   | 0°                  |
| BEAM ANGLE         | 15°                 |
| INT/EXT IP DEGREE  | IP 23               |
| MATERIAL           | Aluminum            |
| IK DEGREE          | IK 6                |
| UTILIZATION        | Indoor              |
| WARRANTY           | 5 years             |

## ELECTRICAL DETAILS

|                        |           |
|------------------------|-----------|
| LAMP                   | LED       |
| POWER                  | 6 W       |
| COLOUR TEMPERATURE     | 3000K     |
| LUMINOUS FLUX          | 520 Lm    |
| EFFICACY DIMMING       | 74 Lm/W   |
| DIMABLE                | Push      |
| DRIVER                 | Remote    |
| CLASS PROTECTION       | II        |
| COLOUR RENDERING INDEX | CRI>90    |
| VOLTAGE                | 220-240 V |
| CURRENT INTENSITY      | 700 mA    |
| LIFE TIME              | 50.000 h  |

## GENERAL DIMENSIONS

|                         |                  |
|-------------------------|------------------|
| DIMENSIONS              | .01 (123x58mm)   |
| CUT OUT                 | 115x45 mm        |
| HEIGHT                  | h 48.5 mm        |
| DIMENSIONES DE EMBALAJE | 190 × 80 × 85 mm |
| PESO NETO               | 35               |

\*Please might expect a max.15% figure reduction in finishes other than white