

## GENERAL DETAILS

INSTALLATION	recessed with frame
FINISHES ALUMINIUM	Black-White
LIGHT DIRECTION	Orientable
TILTING DEGREES	15°
ROTATION DEGREES	0°
BEAM ANGLE	15°
INT/EXT IP DEGREE	IP 23
MATERIAL	Aluminum
IK DEGREE	IK 6
UTILIZATION	Indoor
WARRANTY	3 years


## ELECTRICAL DETAILS

LAMP	LED
POWER	6 W
COLOUR TEMPERATURE	4000K
LUMINOUS FLUX	560 Lm
EFFICACY DIMMING	80 Lm/W
DIMABLE	No Dim
DRIVER	Remote
CLASS PROTECTION	II
COLOUR RENDERING INDEX	CRI>90
VOLTAGE	220-240 V
FRECUENCIA	50-60 Hz
CURRENT INTENSITY	700 mA
LIFE TIME	50.000 h

## GENERAL DIMENSIONS

DIMENSIONS	123×58 mm
CUT OUT	115×45 mm
HEIGHT	h 48.5 mm
DIMENSIONES DE EMBALAJE	190 × 80 × 85 mm
PESO NETO	35

\*Please might expect a max.15% figure reduction in finishes other than white



**nse tilt**

K51301.01.RF.WH-BK.15.ST.9.40