




nses tilt
K51301.01.RF.WH-BK.30.ST.9.40.DA

GENERAL DETAILS

INSTALLATION	recessed with frame
FINISHES ALUMINIUM	Black-White
LIGHT DIRECTION	Orientable
TILTING DEGREES	15°
ROTATION DEGREES	0°
BEAM ANGLE	30°
INT/EXT IP DEGREE	IP 23
MATERIAL	Aluminum
IK DEGREE	IK 6
UTILIZATION	Indoor
WARRANTY	5 years

ELECTRICAL DETAILS

LAMP	LED
POWER	6 W
COLOUR TEMPERATURE	4000K
LUMINOUS FLUX	560 Lm
EFFICACY DIMMING	80 Lm/W
DIMABLE	DALI
DRIVER	Remote
CLASS PROTECTION	II
COLOUR RENDERING INDEX	CRI>90
VOLTAGE	220-240 V
CURRENT INTENSITY	700 mA
LIFE TIME	50.000 h

GENERAL DIMENSIONS

DIMENSIONS	.01 (123x58mm)
CUT OUT	115x45 mm
HEIGHT	h 48.5 mm
DIMENSIONES DE EMBALAJE	190 × 80 × 85 mm
PESO NETO	35

*Please might expect a max.15% figure reduction in finishes other than white