

# nses tilt

K51301.02.RF.BK-BK.15.ST.9.27

## GENERAL DETAILS

| | |
|---|---|
| INSTALLATION | recessed with frame |
| FINISHES ALUMINIUM | Black-Black |
| LIGHT DIRECTION | Orientable |
| TILTING DEGREES | 15° |
| ROTATION DEGREES | 0º |
| BEAM ANGLE | 15º |
| INT/EXT IP DEGREE | IP 23 |
| MATERIAL | Aluminum |
| IK DEGREE | IK 6 |
| UTILIZATION | Indoor |
| WARRANTY | 5 years |

## ELECTRICAL DETAILS

| | |
|---|---|
| LAMP | LED |
| POWER | 10W |
| COLOUR TEMPERATURE | 2700K |
| LUMINOUS FLUX | 835 Lm |
| EFFICACY DIMMING | 70 Lm/W |
| DIMABLE | No Dim |
| DRIVER | Remote |
| CLASS PROTECTION | II |
| COLOUR RENDERING INDEX | CRI>90 |
| VOLTAGE | 220-240 V |
| CURRENT INTENSITY | 700 mA |
| LIFE TIME | 50.000 h |

## GENERAL DIMENSIONS

| | |
|---|---|
| DIMENSIONS | .02 (167x58mm) |
| CUT OUT | 155x45 mm |
| HEIGHT | h 48.5 mm |
| DIMENSIONES DE EMBALAJE | 155 × 155 × 45 mm |
| PESO NETO | 45 |

*Please might expect a max.15% figure reduction in finishes other than white