



n ses tilt

K51301.02.RF.WH-BK.30.ST.9.27

GENERAL DETAILS

INSTALLATION	recessed with frame
FINISHES ALUMINIUM	Black-White
LIGHT DIRECTION	Orientable
TILTING DEGREES	15°
ROTATION DEGREES	0°
BEAM ANGLE	30°
INT/EXT IP DEGREE	IP 23
MATERIAL	Aluminum
IK DEGREE	IK 6
UTILIZATION	Indoor
WARRANTY	3 years

ELECTRICAL DETAILS

LAMP	LED
POWER	10W
COLOUR TEMPERATURE	2700K
LUMINOUS FLUX	835 Lm
EFFICACY DIMMING	70 Lm/W
DIMABLE	No Dim
DRIVER	Remote
CLASS PROTECTION	II
COLOUR RENDERING INDEX	CRI>90
VOLTAGE	220-240 V
FRECUENCIA	50-60 Hz
CURRENT INTENSITY	700 mA
LIFE TIME	50.000 h

GENERAL DIMENSIONS

DIMENSIONS	167×58 mm
CUT OUT	155×45 mm
HEIGHT	h 48.5 mm
DIMENSIONES DE EMBALAJE	155 × 155 × 45 mm
PESO NETO	45

*Please might expect a max.15% figure reduction in finishes other than white