



**nses tilt**  
K51301.03.RF.BK-BK.45.ST.9.27

## GENERAL DETAILS

INSTALLATION	recessed with frame
FINISHES ALUMINIUM	Black-Black
LIGHT DIRECTION	Orientable
TILTING DEGREES	15°
ROTATION DEGREES	0°
BEAM ANGLE	45°
INT/EXT IP DEGREE	IP 23
MATERIAL	Aluminum
IK DEGREE	IK 6
UTILIZATION	Indoor
WARRANTY	5 years

## ELECTRICAL DETAILS

LAMP	LED
POWER	20 W
COLOUR TEMPERATURE	2700K
LUMINOUS FLUX	1530lm
EFFICACY DIMMING	73 Lm/W
DIMABLE	No Dim
DRIVER	Remote
CLASS PROTECTION	II
COLOUR RENDERING INDEX	CRI>90
VOLTAGE	220-240 V
CURRENT INTENSITY	600 mA
LIFE TIME	50.000 h

## GENERAL DIMENSIONS

DIMENSIONS	.03 (300x58mm)
CUT OUT	290x45 mm
HEIGHT	h 48.5 mm
DIMENSIONES DE EMBALAJE	325 × 80 × 85 mm
PESO NETO	78

\*Please might expect a max.15% figure reduction in finishes other than white