

# nses tilt

K51301.03.RF.BK-BK.45.ST.9.40.DA

## GENERAL DETAILS

| | |
|---|---|
| INSTALLATION | recessed with frame |
| FINISHES ALUMINIUM | Black-Black |
| LIGHT DIRECTION | Orientable |
| TILTING DEGREES | 15° |
| ROTATION DEGREES | 0º |
| BEAM ANGLE | 45º |
| INT/EXT IP DEGREE | IP 23 |
| MATERIAL | Aluminum |
| IK DEGREE | IK 6 |
| UTILIZATION | Indoor |
| WARRANTY | 5 years |

## ELECTRICAL DETAILS

| | |
|---|---|
| LAMP | LED |
| POWER | 20 W |
| COLOUR TEMPERATURE | 4000K |
| LUMINOUS FLUX | 1530lm |
| EFFICACY DIMMING | 73 Lm/W |
| DIMABLE | DALI |
| DRIVER | Remote |
| CLASS PROTECTION | II |
| COLOUR RENDERING INDEX | CRI>90 |
| VOLTAGE | 220-240 V |
| CURRENT INTENSITY | 600 mA |
| LIFE TIME | 50.000 h |

## GENERAL DIMENSIONS

| | |
|---|---|
| DIMENSIONS | .03 (300x58mm) |
| CUT OUT | 290x45 mm |
| HEIGHT | h 48.5 mm |
| DIMENSIONES DE EMBALAJE | 325 × 80 × 85 mm |
| PESO NETO | 78 |

*Please might expect a max.15% figure reduction in finishes other than white