



nse tilt
K51301.03.RF.BK-BK.45.ST.9.40.PC

GENERAL DETAILS

INSTALLATION	recessed with frame
FINISHES ALUMINIUM	Black-Black
LIGHT DIRECTION	Orientable
TILTING DEGREES	15°
ROTATION DEGREES	0°
BEAM ANGLE	45°
INT/EXT IP DEGREE	IP 23
MATERIAL	Aluminum
IK DEGREE	IK 6
UTILIZATION	Indoor
WARRANTY	3 years

ELECTRICAL DETAILS

LAMP	LED
POWER	20 W
COLOUR TEMPERATURE	4000K
LUMINOUS FLUX	1530lm
EFFICACY DIMMING	73 Lm/W
DIMABLE	PHASE CUT
DRIVER	Remote
CLASS PROTECTION	II
COLOUR RENDERING INDEX	CRI>90
VOLTAGE	220-240 V
FRECUENCIA	50-60 Hz
CURRENT INTENSITY	600 mA
LIFE TIME	50.000 h

GENERAL DIMENSIONS

DIMENSIONS	300x58 mm
CUT OUT	290x45 mm
HEIGHT	h 48.5 mm
DIMENSIONES DE EMBALAJE	325 x 80 x 85 mm
PESO NETO	78

*Please might expect a max.15% figure reduction in finishes other than white