



n ses tilt

K51301.03.RF.WH-BK.30.ST.9.27.PC

GENERAL DETAILS

| | |
|--------------------|---------------------|
| INSTALLATION | recessed with frame |
| FINISHES ALUMINIUM | Black-White |
| LIGHT DIRECTION | Orientable |
| TILTING DEGREES | 15° |
| ROTATION DEGREES | 0° |
| BEAM ANGLE | 30° |
| INT/EXT IP DEGREE | IP 23 |
| MATERIAL | Aluminum |
| IK DEGREE | IK 6 |
| UTILIZATION | Indoor |
| WARRANTY | 3 years |

ELECTRICAL DETAILS

| | |
|------------------------|-----------|
| LAMP | LED |
| POWER | 20 W |
| COLOUR TEMPERATURE | 2700K |
| LUMINOUS FLUX | 1630 Lm |
| EFFICACY DIMMING | 78 Lm/W |
| DIMABLE | PHASE CUT |
| DRIVER | Remote |
| CLASS PROTECTION | II |
| COLOUR RENDERING INDEX | CRI>90 |
| VOLTAGE | 220-240 V |
| FRECUENCIA | 50-60 Hz |
| CURRENT INTENSITY | 600 mA |
| LIFE TIME | 50.000 h |

GENERAL DIMENSIONS

| | |
|-------------------------|------------------|
| DIMENSIONS | 300x58 mm |
| CUT OUT | 290x45 mm |
| HEIGHT | h 48.5 mm |
| DIMENSIONES DE EMBALAJE | 325 x 80 x 85 mm |
| PESO NETO | 78 |

*Please might expect a max.15% figure reduction in finishes other than white