

nses
K51300.TK

GENERAL DETAILS

INSTALLATION	Tracklight
FINISHES ALUMINIUM	Black-Black, Black-White
LIGHT DIRECTION	Orientable
TILTING DEGREES	60º
ROTATION DEGREES	360°
BEAM ANGLE	15º, 30º, 45º
INT/EXT IP DEGREE	IP20
MATERIAL	Aluminum
IK DEGREE	IK 6
UTILIZATION	Indoor
WARRANTY	5 years

ELECTRICAL DETAILS

LAMP	LED
POWER	10W, 20 W
COLOUR TEMPERATURE	2700K, 3000K, 4000K
LUMINOUS FLUX	275 Lm, 290 Lm, 635 Lm, 640 Lm, 660 Lm, 1250 Lm, 1280 Lm, 1470 Lm
EFFICACY DIMMING	55 Lm/W, 57 Lm/W, 58 Lm/W, 63 Lm/W, 64 Lm/W, 73 Lm/W
DIMABLE	DALI, No Dim
DRIVER	Integrated
CLASS PROTECTION	II
COLOUR RENDERING INDEX	CRI>90
VOLTAGE	220-240 V
CURRENT INTENSITY	600 mA, 700 mA
LIFE TIME	50.000 h

GENERAL DIMENSIONS

DIMENSIONS	.01 (137x34.5mm), .02 (270x34.5mm)
HEIGHT	h 80 mm
DIMENSIONES DE EMBALAJE	N/A

*Please might expect a max.15% figure reduction in finishes other than white